



## Trust Smart Home ASUN-650 Sun blinds switch - White ML

Switch for wireless control of electric shutters, screens, sun blinds, curtains, etc.

Article number: 71017

Barcode: 8713439710175

GTIN: 08713439710175

### Core content

<b>Brand</b>	Trust Smart Home
<b>Product line</b>	Start line
<b>Product type</b>	Sun blinds switch
<b>Colour</b>	White
<b>Plug country code</b>	ML
<b>Key features</b>	- Works with all electric motors up to 500 Watt - Can be used for wireless control of shutters, screens, sun blinds, curtains, etc.
<b>Package contents</b>	- Sun blinds switch - Manual
<b>System requirements</b>	- Electric motor - Trust Smart Home transmitter

### Marketing

<b>Extended retailer text</b>	<p>The wireless solution for electric motors</p> <p>The ASUN-650 switch for sun blinds is meant to open and close (tubular motors of) electric sun blinds, shutters, Venetian blinds and curtains wirelessly with one or more Trust Switch-in transmitters. You connect this receiver to the electric motor and connect one or more KlikAanKlikUit transmitters to it. Use a transmitter of your choice, for example a remote control or wireless wall switch.</p>
-------------------------------	--

---

From clever solutions to a Smart Home

With the Smart Bridge you lay the foundation for your smart home (and garden). Link all your Trust Switch-in products to the Bridge and operate everything - from lighting to electric curtains - using your smartphone or tablet. Or set your own timers, rules and scenes to fully automate your system. For example, the (garden) lights go on at night when you're on holiday and the central heating boiler is switched off when the CO detector detects a carbon monoxide leak.

---

## Specifications

---

<b>Total weight</b>	97 g
<b>Weight of main unit</b>	53 g
<b>Height of main product (in mm)</b>	24 mm
<b>Width of main product (in mm)</b>	50 mm
<b>Depth of main product (in mm)</b>	50 mm
<b>Indicators</b>	Activity
<b>Input frequency of main device</b>	50 Hz
<b>Input voltage of main device</b>	230 V
<b>Max number of transmitters suppo...</b>	32
<b>Intended installation</b>	build-in
<b>Possible to connect traditional ...</b>	false
<b>Required electrical power wires</b>	220V Null
<b>Supports stairwell circuit</b>	false
<b>Wireless protocols</b>	433 MHz

---

**Wireless range** 50 m

---

**Code system** Automatic

---

**Start Line Product type** receiver

---

**Output voltage** 230

---

**Power output** true

---

**Total max output power (W)** 100 Watt

---

**Compatible Product Lines** Start Line

---

## Main image

---



**71017\_pictures\_product\_visual\_1.png**

ImageWidth: 2.500 px

ImageHeight: 2.500 px

ImageResolution: 300 dpi

---

## Additional Product Images

---



**71017\_pictures\_product\_back\_1.png**

ImageWidth: 2.500 px

ImageHeight: 2.500 px

ImageResolution: 300 dpi

---



**71017\_pictures\_product\_front\_1.png**

ImageWidth: 2.500 px

ImageHeight: 2.500 px

ImageResolution: 300 dpi

---

## Product Pictorials



**71017\_EN\_pictures\_product\_pictorial\_1.tiff**

ImageWidth: 6.945 px

ImageHeight: 6.945 px

ImageResolution: 200 dpi

---