

**#71213**

### Atenuador LED integrado

Atenuador LED integrado de alto rendimiento para controlar las luces de forma inalámbrica

#### Características

- La mejor solución para atenuar luces de forma inalámbrica (hasta 50 W)
- También compatible con luces halógenas e incandescentes (hasta 250 W)
- Puede elegir entre 2 modos distintos de atenuación para un rendimiento óptimo de atenuación LED (corte de fase ascendente/descendente)
- Diseño compacto: se puede instalar fácilmente en un techo o una caja de empalmes
- Puede conectar hasta 2 interruptores de pared existentes, por ejemplo, en la parte superior e inferior de una escalera
- Los interruptores de pared existentes siguen operativos



### Qué hay en la caja

- Atenuador LED integrado
- Manual

### Requisitos del sistema

- Transmisor Trust Smart Home
- Luz atenuable LED/incandescente/halógena

**GENERAL**

Height of main product (in mm)	45 mm	Width of main product (in mm)	40 mm
Depth of main product (in mm)	15.2 mm	Total weight	193 g
Weight of main unit	79 g		

**POWER ADAPTER**

Power adapter included	False
------------------------	-------

**POWER OUTPUT**

Number of power output channels	1	Power conversion main component	MOSFET
---------------------------------	---	---------------------------------	--------

**33**

Code system	Automatic	Start Line Product type	Receiver
-------------	-----------	-------------------------	----------

**IMMER**

Dimming modulation	Leading-edge, trailing-edge
--------------------	-----------------------------

**BUILD-IN**

Intended installation	Build-in	Number of traditional wall switches supported	2
Possible to connect traditional wall socket	False	Possible to connect traditional wall switch	True
Required electrical power wires	220V, Null	Supports stairwell circuit	True

**RECEIVER**

Max number of transmitters supported	32
--------------------------------------	----

**OUTPUT**

Power output	True	Output voltage	230
Max power per supported lamp/device type	20-250W Resistive load , 3-50W Dimmable ESL/LED	Total max output power (W)	250 Watt

**ELECTRONIC**

Standby power	1 W	Input frequency of main device	50 Hz
Input voltage of main device	230 V		

**LAMP**

Dimming range	10 - 100 %
---------------	------------

CONNECTIVITY


Cables included	No	Wireless range	40 m
-----------------	----	----------------	------

CONTROL

Controls	Lights on/off	Indicators	Power
----------	---------------	------------	-------

COMPATIBILITY

Compatible Product Lines	Start Line
--------------------------	------------



**PRODUCT VISUAL 1**



**PRODUCT ESHOT 1**



**PRODUCT TOP 1**



**PRODUCT SIDE 1**



**PACKAGE FRONT 1**